

Deriving Atmospheric Winds from GOES-R ABI Measurements

Jaime Daniels

Center for Satellite Applications and Research

National Environmental Satellite Data and Information Surface

National Oceanic and Atmospheric Administration



Outline

- Atmospheric motion as observed from satellite imagery
- Importance of satellite wind observations
- How is atmospheric motion derived from satellite imagery?
- Product examples and assessing product quality
- Who are the users of the satellite derived motion winds product?
- High resolution satellite winds



Longwave Infrared (11um) Band

GOES


The movement of clouds reflects atmospheric motion

Animation of a sequence of satellite images taken at different times reveals the motion

We see it everyday on our local weather TV broadcast, in our favorite weather app, on the internet, etc



Visible (0.64um) Band



GOES

The movement of clouds reflects atmospheric motion


Animation of a sequence of satellite images taken at different times reveals the motion

We see it everyday on our local weather TV broadcast, in our favorite weather app, on the internet, etc



Water vapor (6.5um) Band

GOES




The movement of clouds reflects atmospheric motion

Animation of a sequence of satellite images taken at different times reveals the motion

We see it everyday on our local weather TV broadcast, in our favorite weather app, on the internet, etc



Water vapor (6.7um) Band



Terra/MODIS

The movement of clouds reflects atmospheric motion

Animation of a sequence of satellite images taken at different times reveals the motion


We see it everyday on our local weather TV broadcast, in our favorite weather app, on the internet, etc

GOES-R Brown Bag Seminar, August 27, 2014



Strengths of Geostationary Imagery for Deriving Atmospheric Winds

- View same location on the earth
- Frequent observations!!!
- Improving spatial and spectral resolutions







Importance of Satellite Wind Observations

Satellite Derived Winds are a Key Component of the Global Observing System (GOS)

- Provide vital tropospheric wind information over expansive regions of the earth that are devoid of in-situ wind observations that include oceans, polar regions, and Southern Hemisphere land masses.
- Provide key wind observations to operational NWP data assimilation systems where their use has been demonstrated to improved numerical weather prediction forecasts including tropical cyclones
- Provide improved guidance for NWS field forecasters

Global Radiosonde Network





Aircraft Winds




Importance of Satellite Wind Observations


Satellite Derived Winds are a Key Component of the Global Observing System (GOS)

- Provide vital tropospheric wind information over expansive regions of the earth that are devoid of in-situ wind observations that include oceans, polar regions, and Southern Hemisphere land masses.
- Provide key wind observations to operational NWP data assimilation systems where their use has been demonstrated to improved numerical weather prediction forecasts including tropical cyclones
- Provide improved guidance for NWS field forecasters

Global Radiosonde Network



Global Geostationary Satellite Coverage







Importance of Satellite Wind Observations

Satellite Derived Winds are a Key Component of the Global Observing System (GOS)

- Provide vital tropospheric wind information over expansive regions of the earth that are devoid of in-situ wind observations that include oceans, polar regions, and Southern Hemisphere land masses.
- Provide key wind observations to operational NWP data assimilation systems where their use has been demonstrated to improved numerical weather prediction forecasts including tropical cyclones
- Provide improved guidance for NWS field forecasters

Global Radiosonde Network






GOES-R Brown Bag Seminar, August 27, 2014




How is Atmospheric Motion Derived from Satellite Imagery?

How do we quantify the observed motion into speed, direction, and height?

Longwave Infrared (11um) Band








- Select a target
- Track the movement of each target over time
- Assign a height to each target
- Quality Control



• Select a target


- Track the movement of each target over time
- Assign a height to each target
- Quality Control



- A "target" scene is a NxN array or patch of pixels
- This array of pixels is what is tracked over time to estimate the wind
- Cloud edges are good targets



- Select a target
- Track the movement of each target over time
- Assign a height to each target
- Quality Control



- A sequence of three images is used
- The speed and direction of each target can be computed since we know the location and time of the target in each image




Illustration of Feature Tracking



<u>2nd Image:</u> Time = t_0

- Targeting is performed on the <u>center</u> image of image triplet
- A target is a NxN scene of pixels









Illustration of Feature Tracking



<u>1st Image:</u> Time = t_0 - 10mins

Feature is found and tracked at an <u>earlier</u> time










Illustration of Feature Tracking



<u>3rd Image:</u> Time = t_0 + 10mins


 Feature is found and tracked <u>later</u> in time







- Select a target
- Track the movement of each target over time
- Assign a height to each target
- Quality Control



• Cloud top heights generated before the winds algorithm runs are used to assign heights to each target



- Select a target
- Track the movement of each target over time
- Assign a height to each target
- Quality Control



- Flag suspect winds
- Compute and append quality indicators to each retrieved wind



How will the GOES-R ABI improve our ability to retrieve better wind products?

Improved Temporal Resolution (Faster Scanning)


In 15 Minutes the current GOES Imager can scan: • Most (3/5) of a Full Disk (Hemisphere) Image


ABI scans about 5 times faster than the current GOES imager


In 15 Minutes the ABI (Flex Mode) will scan:

- 30 Images of localized severe weather events
- 3 Images of the Continental US
- 1 Full DiskImage

Current GOES Imager







GOES-R Brown Bag Seminar, August 27, 2014



How will the GOES-R ABI improve our ability to retrieve better wind products?

Improved Navigation and Registration

Will lead to a more accurate wind product

GOES-15 provides a hint of ABI's INR quality...






How will the GOES-R ABI improve our ability to retrieve better wind products?

Improved Radiometric Performance together with Improved Spectral and Spatial Resolution

Will lead to improved wind height assignments and a more accurate wind product






PRODUCT EXAMPLES




Meteosat-10/SEVIRI FD Winds


LWIR (10.8um)







- New nested tracking algorithm introduced that makes use of a twodimensional clustering algorithm to capture the dominant motion in each target scene
- Utilizes clear sky mask product
- Wind height assignment relies on the utilization of pixel level cloud heights generated upstream
- Running in real-time









NASA (1000)

Application of GOES-R Winds Algorithm to Meteosat/SEVIRI


Loop of winds derived from hourly Full Disk Meteosat-9 SEVERI 10.8 μm imagery (22 UTC Apr 24 – 08 UTC Apr 25, 2012

High-Level 100-400 mb Mid-Level 400-700 mb

Low-Level >700 mb


Application of GOES-R Winds Algorithm to Current GOES

Cloud-drift winds derived from 15-min GOES-15 imagery over the East Pacific




Application of GOES-R Winds Algorithm to Current GOES

Cloud-drift winds derived from 15-min GOES-13 imagery over Hurricane Sandy (4-day loop)



The GOES-R Winds Team continues to routinely generate and validate ABI proxy winds from GOES-13,GOES-15, Meteosat-10/SEVIRI, and NPP/VIIRS using the GOES-R winds algorithm.28

Application of GOES-R Winds Algorithm to Simulated GOES-R ABI Imagery



High-Level 100-400 mb

Mid-Level 400-700 mb

Low-Level >700 mb


29



Winds from VIIRS Derived from the GOES-R Winds Algorithm

 The VIIRS polar winds product became <u>operational in NESDIS</u> <u>on 8 May 2014</u>.

 This is the first GOES-R algorithm to become operational.





Assessing the Quality of Satellite Derived Winds

Radiosonde Wind Observations

 Used by all operational satellite processing centers that generate satellite derived motion winds




- Useful over ocean
- Aircraft Communications and Addressing System (ACARS) Wind Observations






³⁰⁰ mb Height and Winds (kt) 2230 UTC 06/04/05





Assessing the Quality of Satellite Derived Winds (vs radiosondes)





Who are the Users of the Satellite Derived Motion Winds Product?


• Field Forecasters (NWS WFOs and National Centers)

- Situational awareness of the atmospheric wind field
- Verification of model guidance
- Atmospheric monitoring

Numerical Weather Prediction Centers

- NWS/NCEP and international NWP centers are <u>primary</u> <u>users</u>
- Satellite winds used to support the initialization of the atmospheric wind field in global and regional models


General Forecast Process: Observations to Human Forecast



Human-Generated Forecast

Valid 12Z Wed Nov 20 2013 - 1

Satellite Winds within the NWS Advanced Weather Interactive Processing System (AWIPS)




Verification of a Strong Polar Jet:

250mb GOES Water Vapor Winds, radiosonde winds, and NCEP NAM model forecast isotachs

GOES winds as displayed in AWIPS

AWIPS enables easy integration of GOES AMVs with a multitude of other data sources



ir Satellite kmkx Radar	SCAN	Maps SSEC Help	WamGe	n
IR Window	29.2030	🖌 Mag: 1.25 💻 Density: Max 🗸	-	
Water Vapor	29.2015			
Visible	29.1745			
4 3.9u		<u> </u>		
13u				
11u-3.9u				
11u-13u				
ww/ir				
4 panel (GOES M-Q)				
		P F ZF		
POES Imagery				
IR Window		Et Int	A DESCRIPTION OF THE OWNER OF THE	
Visible		E FIFE	Alm Y	-
3.7u			The second secon	
11-3.7u		F JEA	William William	
Sounder Imagery	Þ			
Derived Products Imagery	Þ			
Derived Products Plots	4		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
NH/NA/US every image		GOES High Density Winds	and the state of	
IR Window	29.2030	MTSAT High Density Winds		
Water Vapor	29.2030	Scatterometer Winds	Satellite-Derived who:	- 24
Visible	29.2030	SSM/I Point Data	IR Plot	23
3.90	23.2030	GOES Sounding Availability	Water Vapor Plot	23
13u		POES Sounding Availability	Visible Plot	23
11u-3.9u		and the second s	IR 3.9u Plot	23
11u-13u		All and a second	Satellite Layer Winds	
WV/IR	29.2030	Netty part fifthe Dat Dear	200hPa Layer Plot	23
	23.2030	the sub-	250hPa Layer Plot	23
4 Sat Composite		MILL IN ALLAND A THE	300hPa Layer Plot	23
IR Window	29.1800	All All All All All	400hPa Layer Plot	23
Water Vapor	29.1800	A A A A A A A A A A A A A A A A A A A	500hPa Layer Plot	23
	29.1800	A centering Martin	700hPa Layer Plot	
📰 Visible				6
Visible WV/IR	29.1800	- Internet - and the first of	850hPa Layer Plot	23

Beginning in October 2008, "high density winds" (also known as Atmospheric Motion Vectors, or AMVs) derived from the Japanese geostationary Multi-functional Transport Satellite (MTSAT-1R, which is positioned over the Equator at 140º East longitude) were added to the NOAAPORT Satellite Broadcast Network (SBN). National Weather Service forecast offices localized as West CONUS sites (or OCONUS offices in the Alaska Region and the Pacific Region) that have installed AWIPS Operational Build 9.0 or higher will be able to access these new MTSAT satellite winds products from the AWIPS menu (above).

TECHNICAL IMPLEMENTATION NOTICE 08-61 NATIONAL WEATHER SERVICE HEADQUARTERS WASHINGTON DC 317 PM EDT FRI AUG 1 2008

SUBJECT: NESDIS HIGH DENSITY GEOSTATIONARY WINDS TO BE

.2000

.2000

.2000

.2000

.2000

.2000

.2000

.2000

.2000

.2000

.2000

102:00Z 29-Jan-09

ADDED TO SBN/NOAAPORT: EFFECTIVE OCTOBER 15 2008

EFFECTIVE WEDNESDAY OCTOBER 15 2008...BEGINNING AT APPROXIMATELY 1500 COORDINATED UNIVERSAL TIME /UTC/...THE NATIONAL ENVIRONMENTAL SATELLITE...DATA...AND INFORMATION SERVICE /NESDIS/ AND NWS START DISSEMINATING HIGH DENSITY GEOSTATIONARY /MTSAT/ WIND PRODUCTS VIA SBN/NOAAPORT.

THE MTSAT WINDS /FROM THE JAPANESE SATELLITE/ WILL AUGMENT THE CURRENT GOES EAST AND WEST HIGH DENSITY WINDS OVER SPARSE DATA REGIONS...MOST BENEFITING THE ALASKA AND PACIFIC REGIONS CENAND THE AVIATION WEATHER TER /AWC/.



Use of Water Vapor Imagery and GOES Winds at NHC

Tropical Storm Cristobal 25 Aug 2014 13 UTC

100-250 mb 250-350 mb

The AMVs are used to help identify synoptic patterns, assess outflow and shear around tropical cyclones, and, when displayed on model fields, to help assess the reliability of the model initial conditions


50-350 140825/1300 FREFFigure courtesy of Mark DeMaria (NWS/NHC)



Coordinated Study of AMV Impact *Highlights from IWWG Study...*

Forecast Sensitivity to Observations (FSO)

- Adjoint-based FSO method gives estimate of the contribution of each observation towards reducing the 24-hour forecast error
- Satellite winds reduce 24 hour forecast error on the order of 7-11% (NRL was exception)
- Places satellite winds among the top global observing system observations that contribute in a positive way to NWP global forecast impact







Higher Resolution Satellite Winds A Hot, Hot Area of Ongoing Research...

- Current AMV products generally designed to capture broad-scale to synoptic scale flow. However, NWP is moving to higher spatial resolution and more frequent assimilation cycles.
- There is information available on smaller scales in the geo satellite imagery (i.e. *clearly evident in rapid-scan animations*)
- Future instruments (GOES-R ABI, Himawari-8, etc) will bring improved spectral, spatial, and temporal resolution, all of which will enable the generation of higher resolution AMV products
- Can we derive more useful AMV information for nowcasting and mesoscale assimilation in high resolution models like NCEP's HWRF to help with forecasting <u>high impact weather events like tropical cyclones?</u>



GOES-14 SRSOR of Sandy (Visible)





http://cimss.ssec.wisc.edu/goes/srsor/GOES-14_SRSOR.html

Hurricane force winds (> 75 mph)

20002 G-14 IMG 1 28 OCT 12302 160500 04117 16962 01.00

Hurricane Sandy



Summary

- Atmospheric motion is readily apparent in sequences of satellite imagery
- Satellite derived winds are a key component of the Global Observing System (GOS)
- GOES-R ABI will improve our ability to retrieve better wind products
- User community (NWP users, field forecasters) will benefit from better wind products



Questions



Jaime Daniels: jaime.daniels@noaa.gov

NESDIS STAR AWG web page: <u>http://www.star.nesdis.noaa.gov/goesr</u> 43

Hurricane force winds (> 75 mph)

20002 G-14 IMG 1 28 OCT 12302 160500 04117 16962 01.00

Hurricane Sandy




BACKUP




Validation Strategy For satellite wind height assignments...


Using CALIPSO/CloudSat Data to Validate Satellite Wind Height Assignments

- Leverages unprecedented cloud information offered by CALIPSO and CloudSat measurements
- Enables improved error characterization of satellite wind height assignments
- Enables feedback for potential improvements to satellite wind height assignments
- Improvements to overall accuracy of satellite-derived winds



GOES-12 Cloud-drift Wind Heights Overlaid on CALIPSO total attenuated backscatter image at 532nm





Hurricane Isabel

GOES-12 Vis imagery 12 Sept. 2003

Low-level AMVs in Isabel's eye derived from GOES-12 <u>super-rapid-scan</u> (3-min intervals used) VIS imagery



Data assimilation systems

Data assimilation systems produce the starting point or analysis for an NWP forecast. To do this, they take a short-range NWP forecast or first guess valid at the analysis time, and use observations within a time window centered on that time to adjust the first guess to the best analysis possible. This becomes the starting place for the current forecast cycle.

Forecast modules

The forecast part of the NWP model consists of two modules. One deals with dynamical equations, the other with physical parameterizations. Dynamical equations forecast processes that are large enough to be analyzed and forecast at the model's resolution, such as shortwave troughs. Physical parameterizations estimate the effect of processes that are smaller than the model can forecast directly, such as convection and atmospheric transmission of long- and shortwave radiation.

Observations from new instruments

The needs of DA systems and NWP help drive new instrument design. Observations from new instruments are quality tested before and after launch. They are then tested in the DA system, and NWP forecasts are run from these test analyses. If the quality of the forecasts improves or is maintained, the new data are accepted for operational use. Otherwise, they will not be used.

All satellite data are continuously monitored, even after they are accepted into operations. Any degradation in data quality is corrected if possible. Otherwise, the data are removed from the DA observational stream. Other satellites with the same or similar instruments may be considered to replace the lost data.

Satellite observations and retrievals

Satellite data are assimilated operationally in two forms, as observations and as retrievals. When retrieval products are used, they are compared directly to the matching first guess data to determine an analysis increment. When observations are used, the first guess data is converted into simulated satellite observations and adjusted to bring it and the actual observations as close to each other as possible. These adjustments are then used as analysis increments. From this point forward, observations and retrievals are handled in the same manner: weighted, buddy checked, and weight adjusted if they're significantly different from neighboring increments. In the last step, the increments from all observational platforms are combined to make the final analysis.

Satellite data are essential for making good forecasts in high-impact situations, and for improving overall model forecast skill. This is especially true in and downstream from data-sparse areas.

Future challenges

To improve satellite data and NWP and DA systems in the future, challenges need to be met in three areas. **NWP models** and their **DA systems** need to make better use of existing satellite data, particularly in the areas of clouds and precipitation, explicitly predicted convection, natural and human-made aerosols, and real-time surface conditions such as soil moisture and vegetation greenness. Preparatory work needs to continue so the satellite observations from GOES-R and the next generation of NOAA LEO satellites will be used effectively.

In the area of **satellite remote sensing**, we need to increase the resolution of microwave sounders, improve the usefulness of sounder data in areas of clouds and precipitation, increase the amount of satellite wind data, and add hyperspectral infrared instruments to geostationary satellites. In addition, we need to address the potential loss of U.S. LEO data if there's a gap between the decommissioning of any current satellites and the launch of next generation satellites.